

MATERIALS

- 1. INSULATOR : TEFLON UL94V-0, WHITE
- 2. BODY : BRASS, GOLD PLATED
- 3. CONTACT : PHOSPHOR BRONZE

OTHER INFORMATION


- 1. CONTACT RESISTANCE : 5.0m OHMS MAX.
- 2. DIELECTRIC WITHSTANDING VOLTAGE : 500V AC RMS FOR 1 MINUTE
- 3. INSULATION RESISTANCE : 1000M OHMS MIN. AT 500V DC
- 4. OPERATING TEMPERATURE : -40°C ~ +90°C

PART NUMBER

53BE - 1 1 - 1 5 1 - 0 4 6

- SERIES
- CONTACT PLATED
- 1: GOLD FLASH
- BODY PLATED
- 1: GOLD FLASH

RECOMMEND P.C.B. LAYOUT
TOP VIEW



CABLESLINK TECHNOLOGIES CO., LTD.
TEL:886 3 4990325 FAX:886 3 4990295

TOLERANCES		SMA SERIES	
X.X	±0.2	PCB MOUNT, RIGHT ANGLE	
X.XX	±0.15	50 OHM	
X.XXX	±0.1		
Angle ±5°			
DRAWN BY		CHECKED BY	
APPROVED BY			
UNIT	SCALE	SIZE	DRAW NO.
MM	NONE	A4	D063-BE046
REV.		REV.	
A	0822,2015	A	
RELEASE			
DESCRIPTION			
04130			