

MAX 10 FPGA Device Datasheet

2015.01.23

M10-DATASHEET

 Subscribe

 Send Feedback

This datasheet describes the electrical characteristics, switching characteristics, configuration specifications, and timing for MAX® 10 devices.

Table 1: MAX 10 Device Grades and Speed Grades Supported

Device Grade	Speed Grade Supported
Commercial	<ul style="list-style-type: none">-C7-C8 (slowest)
Industrial	<ul style="list-style-type: none">-I6 (fastest)-I7
Automotive	-A7

Note: The -I6 speed grade MAX 10 FPGA device option is not available by default in the Quartus® II software. Contact your local Altera sales representatives for support.

Related Information

[MAX 10 FPGA Device Overview](#)

Provides more information about the densities and packages of devices in the MAX 10.

Electrical Characteristics

The following sections describe the operating conditions and power consumption of MAX 10 devices.

© 2015 Altera Corporation. All rights reserved. ALTERA, ARRIA, CYCLONE, ENPIRION, MAX, MEGACORE, NIOS, QUARTUS and STRATIX words and logos are trademarks of Altera Corporation and registered in the U.S. Patent and Trademark Office and in other countries. All other words and logos identified as trademarks or service marks are the property of their respective holders as described at www.altera.com/common/legal.html. Altera warrants performance of its semiconductor products to current specifications in accordance with Altera's standard warranty, but reserves the right to make changes to any products and services at any time without notice. Altera assumes no responsibility or liability arising out of the application or use of any information, product, or service described herein except as expressly agreed to in writing by Altera. Altera customers are advised to obtain the latest version of device specifications before relying on any published information and before placing orders for products or services.

ISO
9001:2008
Registered

Operating Conditions

MAX 10 devices are rated according to a set of defined parameters. To maintain the highest possible performance and reliability of the MAX 10 devices, you must consider the operating requirements described in this section.

Absolute Maximum Ratings

This section defines the maximum operating conditions for MAX 10 devices. The values are based on experiments conducted with the devices and theoretical modeling of breakdown and damage mechanisms. The functional operation of the device is not implied for these conditions.

Caution: Conditions outside the range listed in the absolute maximum ratings tables may cause permanent damage to the device. Additionally, device operation at the absolute maximum ratings for extended periods of time may have adverse effects on the device.

Single Supply Devices Absolute Maximum Ratings

Table 2: Absolute Maximum Ratings for MAX 10 Single Supply Devices—Preliminary

Symbol	Parameter	Min	Max	Unit
V _{CC_ONE}	Supply voltage for core and periphery through on-die voltage regulator	-0.5	3.9	V
V _{CCIO}	Supply voltage for input and output buffers	-0.5	3.9	V
V _{CCA}	Supply voltage for phase-locked loop (PLL) regulator and analog-to-digital converter (ADC) block (analog)	-0.5	3.9	V

Dual Supply Devices Absolute Maximum Ratings

Table 3: Absolute Maximum Ratings for MAX 10 Dual Supply Devices—Preliminary

Symbol	Parameter	Min	Max	Unit
V _{CC}	Supply voltage for core and periphery	-0.5	1.63	V
V _{CCIO}	Supply voltage for input and output buffers	-0.5	3.9	V
V _{CCA}	Supply voltage for PLL regulator (analog)	-0.5	3.41	V
V _{CCD_PLL}	Supply voltage for PLL regulator (digital)	-0.5	1.63	V

Symbol	Parameter	Min	Max	Unit
V _{CCA_ADC}	Supply voltage for ADC analog block	-0.5	3.41	V
V _{CCINT}	Supply voltage for ADC digital block	-0.5	1.63	V

Absolute Maximum Ratings

Table 4: Absolute Maximum Ratings for MAX 10 Devices—Preliminary

Symbol	Parameter	Min	Max	Unit
V _I	DC input voltage	-0.5	4.12	V
I _{OUT}	DC output current per pin	-25	25	mA
T _{STG}	Storage temperature	-65	150	°C
T _J	Operating junction temperature	-40	125	°C

Maximum Allowed Overshoot During Transitions over a 11.4-Year Time Frame

Table 5: Maximum Allowed Overshoot During Transitions over a 11.4-Year Time Frame for MAX 10 Devices

Condition (V)	Overshoot Duration as % of High Time	Unit
4.12	100.0	%
4.17	11.7	%
4.22	7.1	%
4.27	4.3	%
4.32	2.6	%
4.37	1.6	%
4.42	1.0	%
4.47	0.6	%
4.52	0.3	%

Condition (V)	Overshoot Duration as % of High Time	Unit
4.57	0.2	%

Recommended Operating Conditions

This section lists the functional operation limits for the AC and DC parameters for MAX 10 devices. The tables list the steady-state voltage values expected from MAX 10 devices. Power supply ramps must all be strictly monotonic, without plateaus.

Single Supply Devices Power Supplies Recommended Operating Conditions

Table 6: Power Supplies Recommended Operating Conditions for MAX 10 Single Supply Devices—Preliminary

Symbol	Parameter	Condition	Min	Typ	Max	Unit
$V_{CC_ONE}^{(1)}$	Supply voltage for core and periphery through on-die voltage regulator	—	2.85/3.135	3.0/3.3	3.15/3.465	V
$V_{CCIO}^{(2)}$	Supply voltage for input and output buffers	3.3 V	3.135	3.3	3.465	V
		3.0 V	2.85	3	3.15	V
		2.5 V	2.375	2.5	2.625	V
		1.8 V	1.71	1.8	1.89	V
		1.5 V	1.425	1.5	1.575	V
		1.35 V	1.2825	1.35	1.4175	V
		1.2 V	1.14	1.2	1.26	V
$V_{CCA}^{(1)}$	Supply voltage for PLL regulator and ADC block (analog)	—	2.85/3.135	3.0/3.3	3.15/3.465	V

⁽¹⁾ V_{CCA} must be connected to V_{CC_ONE} through a filter.

⁽²⁾ V_{CCIO} for all I/O banks must be powered up during device operation.

Dual Supply Devices Power Supplies Recommended Operating Conditions

Table 7: Power Supplies Recommended Operating Conditions for MAX 10 Dual Supply Devices—Preliminary

Symbol	Parameter	Condition	Min	Typ	Max	Unit
V _{CC}	Supply voltage for core and periphery	—	1.15	1.2	1.25	V
V _{CCIO} ⁽³⁾	Supply voltage for input and output buffers	3.3 V	3.135	3.3	3.465	V
		3.0 V	2.85	3	3.15	V
		2.5 V	2.375	2.5	2.625	V
		1.8 V	1.71	1.8	1.89	V
		1.5 V	1.425	1.5	1.575	V
		1.35 V	1.2825	1.35	1.4175	V
		1.2 V	1.14	1.2	1.26	V
V _{CCA} ⁽⁴⁾	Supply voltage for PLL regulator (analog)	—	2.375	2.5	2.625	V
V _{CCD_PLL} ⁽⁵⁾	Supply voltage for PLL regulator (digital)	—	1.15	1.2	1.25	V
V _{CCA_ADC}	Supply voltage for ADC analog block	—	2.375	2.5	2.625	V
V _{CCINT}	Supply voltage for ADC digital block	—	1.15	1.2	1.25	V

Recommended Operating Conditions

Table 8: Recommended Operating Conditions for MAX 10 Devices—Preliminary

Symbol	Parameter	Condition	Min	Max	Unit
V _I	DC input voltage	—	-0.5	3.6	V

⁽³⁾ V_{CCIO} for all I/O banks must be powered up during device operation.

⁽⁴⁾ All V_{CCA} pins must be powered to 2.5 V (even when PLLs are not used), and must be powered up and powered down at the same time.

⁽⁵⁾ V_{CCD_PLL} must always be connected to V_{CC} through a decoupling capacitor and ferrite bead.

Symbol	Parameter	Condition	Min	Max	Unit
V_O	Output voltage for I/O pins	—	0	V_{CCIO}	V
T_J	Operating junction temperature	Commercial	0	85	°C
		Industrial	-40	100	°C
		Automotive	-40	125	°C
t_{RAMP}	Power supply ramp time	Standard POR ⁽⁶⁾	200 µs	50 ms	—
		Fast POR ⁽⁷⁾	200 µs	3 ms	—
		Instant-on	200 µs	3 ms	—
I_{Diode}	Magnitude of DC current across PCI clamp diode when enabled	—	—	10	mA

Programming/Erasure Specifications

Table 9: Programming/Erasure Specifications for MAX 10 Devices—Preliminary

This table shows the programming cycles and data retention duration of the user flash memory (UFM) and configuration flash memory (CFM) blocks.

Erase and reprogram cycles (E/P) ⁽⁸⁾ (Cycles/page)	Temperature (°C)	Data retention duration (Years)
10,000	85	20
10,000	100	10

DC Characteristics

I/O Pin Leakage Current

The values in the table are specified for normal device operation. The values vary during device power-up. This applies for all V_{CCIO} settings (3.3, 3.0, 2.5, 1.8, 1.5, 1.35, and 1.2 V).

⁽⁶⁾ Each individual power supply should reach the recommended operating range within 50 ms.

⁽⁷⁾ Each individual power supply should reach the recommended operating range within 3 ms.

⁽⁸⁾ The number of E/P cycles applies to the smallest possible flash block that can be erased or programmed in each MAX 10 device. Each MAX 10 device has multiple flash pages per device.

10 μ A I/O leakage current limit is applicable when the internal clamping diode is off. A higher current can be observed when the diode is on.

Input channel leakage of ADC I/O pins due to hot socket is up to maximum of 1.8 mA. The input channel leakage occurs when the ADC IP core is enabled or disabled. This is applicable to all MAX 10 devices with ADC IP core, which are 10M04, 10M08, 10M16, 10M25, 10M40, and 10M50 devices. The ADC I/O pins are in Bank 1A.

Table 10: I/O Pin Leakage Current for MAX 10 Devices—Preliminary

Symbol	Parameter	Condition	Min	Max	Unit
I_I	Input pin leakage current	$V_I = 0 \text{ V to } V_{CCIO_{MAX}}$	-10	10	μA
I_{OZ}	Tristated I/O pin leakage current	$V_O = 0 \text{ V to } V_{CCIO_{MAX}}$	-10	10	μA

Bus Hold Parameters

Bus hold retains the last valid logic state after the source driving it either enters the high impedance state or is removed. Each I/O pin has an option to enable bus hold in user mode. Bus hold is always disabled in configuration mode.

Table 11: Bus Hold Parameters for MAX 10 Devices—Preliminary

Parameter	Condition	$V_{CCIO} (\text{V})$												Unit	
		1.2		1.5		1.8		2.5		3		3.3			
		Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
Bus-hold low, sustaining current	$V_{IN} > V_{IL}$ (maximum)	8	—	12	—	30	—	50	—	70	—	70	—	μA	
Bus-hold high, sustaining current	$V_{IN} < V_{IL}$ (minimum)	-8	—	-12	—	-30	—	-50	—	-70	—	-70	—	μA	
Bus-hold low, overdrive current	$0 \text{ V} < V_{IN} < V_{CCIO}$	—	125	—	175	—	200	—	300	—	500	—	500	μA	
Bus-hold high, overdrive current	$0 \text{ V} < V_{IN} < V_{CCIO}$	—	-125	—	-175	—	-200	—	-300	—	-500	—	-500	μA	
Bus-hold trip point	—	0.3	0.9	0.375	1.125	0.68	1.07	0.7	1.7	0.8	2	0.8	2	V	

Series OCT without Calibration Specifications

Table 12: Series OCT without Calibration Specifications for MAX 10 Devices—Preliminary

This table shows the variation of on-chip termination (OCT) without calibration across process, voltage, and temperature (PVT).

Description	V _{CCIO} (V)	Resistance Tolerance		Unit
		-C7, -I6, -I7, -A7	-C8	
Series OCT without calibration	3.00	±35	±30	%
	2.50	±35	±30	%
	1.80	±40	±35	%
	1.50	±40	±40	%
	1.35	±40	±50	%
	1.20	±45	±60	%

Series OCT with Calibration at Device Power-Up Specifications

Table 13: Series OCT with Calibration at Device Power-Up Specifications for MAX 10 Devices—Preliminary

OCT calibration is automatically performed at device power-up for OCT enabled I/Os.

Description	V _{CCIO} (V)	Calibration Accuracy	Unit
Series OCT with calibration at device power-up	3.00	±12	%
	2.50	±12	%
	1.80	±12	%
	1.50	±12	%
	1.35	±12	%
	1.20	±12	%

OCT Variation after Calibration at Device Power-Up

The OCT resistance may vary with the variation of temperature and voltage after calibration at device power-up.

Use the following table and equation to determine the final OCT resistance considering the variations after calibration at device power-up.

Table 14: OCT Variation after Calibration at Device Power-Up for MAX 10 Devices—Preliminary

This table lists the change percentage of the OCT resistance with voltage and temperature.

Description	Nominal Voltage	dR/dT (%/°C)	dR/dV (%/mV)
OCT variation after calibraiton at device power-up	3.00	0.25	-0.027
	2.50	0.245	-0.04
	1.80	0.242	-0.079
	1.50	0.235	-0.125
	1.35	0.229	-0.16
	1.20	0.197	-0.208

Figure 1: Equation for OCT Resistance after Calibration at Device Power-Up

$$\Delta R_V = (V_2 - V_1) \times 1000 \times dR/dV$$

$$\Delta R_T = (T_2 - T_1) \times dR/dT$$

For $\Delta R_X < 0$; $MF_X = 1/(|\Delta R_X|/100 + 1)$

For $\Delta R_X > 0$; $MF_X = \Delta R_X/100 + 1$

$$MF = MF_V \times MF_T$$

$$R_{final} = R_{initial} \times MF$$

The definitions for equation are as follows:

- T_1 is the initial temperature.
- T_2 is the final temperature.
- MF is multiplication factor.
- $R_{initial}$ is initial resistance.
- R_{final} is final resistance.
- Subscript x refers to both V and T.
- ΔR_V is variation of resistance with voltage.
- ΔR_T is variation of resistance with temperature.
- dR/dT is the change percentage of resistance with temperature after calibration at device power-up.
- dR/dV is the change percentage of resistance with voltage after calibration at device power-up.
- V_1 is the initial voltage.
- V_2 is final voltage.

The following figure shows the example to calculate the change of 50Ω I/O impedance from 25°C at 3.0 V to 85°C at 3.15 V .

Figure 2: Example for OCT Resistance Calculation after Calibration at Device Power-Up

$$\Delta R_V = (3.15 - 3) \times 1000 \times -0.026 = -3.83$$

$$\Delta R_T = (85 - 25) \times 0.026 = 15.72$$

Because ΔR_V is negative,

$$MF_V = 1/(3.83/100 + 1) = 0.963$$

Because ΔR_T is positive,

$$MF_T = 15.72/100 + 1 = 1.157$$

$$MF = 0.963 \times 1.157 = 1.114$$

$$R_{final} = 50 \times 1.114 = 55.71\Omega$$

Pin Capacitance

Table 15: Pin Capacitance for MAX 10 Devices—Preliminary

Symbol	Parameter	Value	Unit
C_{IOB}	Input capacitance on bottom I/O pins	8	pF
C_{IOLRT}	Input capacitance on left/right/top I/O pins	7	pF
C_{LVDSB}	Input capacitance on bottom I/O pins with dedicated LVDS output ⁽⁹⁾	8	pF
C_{ADCL}	Input capacitance on left I/O pins with ADC input ⁽¹⁰⁾	9	pF
$C_{VREFLRT}$	Input capacitance on left/right/top dual purpose V_{REF} pin when used as V_{REF} or user I/O pin ⁽¹¹⁾	48	pF
C_{VREFB}	Input capacitance on bottom dual purpose V_{REF} pin when used as V_{REF} or user I/O pin	50	pF
C_{CLKB}	Input capacitance on bottom dual purpose clock input pins ⁽¹²⁾	7	pF
C_{CLKLRT}	Input capacitance on left/right/top dual purpose clock input pins ⁽¹²⁾	6	pF

Internal Weak Pull-Up Resistor

All I/O pins, except configuration, test, and JTAG pins, have an option to enable weak pull-up.

⁽⁹⁾ Dedicated LVDS output buffer is only available at bottom I/O bank.

⁽¹⁰⁾ ADC pins are only available at left I/O bank.

⁽¹¹⁾ When V_{REF} pin is used as regular input or output, F_{max} performance is reduced due to higher pin capacitance. Using the V_{REF} pin capacitance specification from device datasheet, perform SI analysis on your board setup to determine the F_{max} of your system.

⁽¹²⁾ 10M40 and 10M50 devices have dual purpose clock input pins at top/bottom I/O banks.

Table 16: Internal Weak Pull-Up Resistor for MAX 10 Devices—Preliminary

Pin pull-up resistance values may be lower if an external source drives the pin higher than V_{CCIO} .

Symbol	Parameter	Condition	Min	Typ	Max	Unit
R _{PU}	Value of I/O pin pull-up resistor before and during configuration, as well as user mode if the programmable pull-up resistor option is enabled	$V_{CCIO} = 3.3 \text{ V} \pm 5\%$	7	12	18	kΩ
		$V_{CCIO} = 3.0 \text{ V} \pm 5\%$	8	13	20	kΩ
		$V_{CCIO} = 2.5 \text{ V} \pm 5\%$	10	15	25	kΩ
		$V_{CCIO} = 1.8 \text{ V} \pm 5\%$	16	25	46	kΩ
		$V_{CCIO} = 1.5 \text{ V} \pm 5\%$	20	36	82	kΩ
		$V_{CCIO} = 1.2 \text{ V} \pm 5\%$	33	82	175	kΩ

The internal weak pull-up resistor is defined in the following equation:

Figure 3: Internal Weak Pull-Up Resistor

$$R_{PU} = (V_{CCIO} - V_I) / I_{R_{PU}}$$

Minimum condition: -40°C ; $V_{CCIO} = V_{CC} + 5\%$; $V_I = V_{CC} + 5\% - 50\text{mV}$;

Typical condition: 25°C ; $V_{CCIO} = V_{CC}$; $V_I = 0 \text{ V}$;

Maximum condition: 125°C ; $V_{CCIO} = V_{CC} - 5\%$; $V_I = 0 \text{ V}$;

where V_I refers to the input voltage at the I/O pin.

Hot-Socketing Specifications

Table 17: Hot-Socketing Specifications for MAX 10 Devices—Preliminary

Symbol	Parameter	Maximum
I _{IOPIN(DC)}	DC current per I/O pin	300 μA

Symbol	Parameter	Maximum
I _{IOPIN(AC)}	AC current per I/O pin	8 mA ⁽¹³⁾

Hysteresis Specifications for Schmitt Trigger Input

MAX 10 devices support Schmitt trigger input on all I/O pins. A Schmitt trigger feature introduces hysteresis to the input signal for improved noise immunity, especially for signal with slow edge rate.

Table 18: Hysteresis Specifications for Schmitt Trigger Input for MAX 10 Devices—Preliminary

Symbol	Parameter	Condition	Minimum	Unit
V _{HYS}	Hysteresis for Schmitt trigger input	V _{CCIO} = 3.3 V	180	mV
		V _{CCIO} = 2.5 V	150	mV
		V _{CCIO} = 1.8 V	120	mV
		V _{CCIO} = 1.5 V	110	mV

⁽¹³⁾ The I/O ramp rate is 10 ns or more. For ramp rates faster than 10 ns, |I_{IOPIN}| = C dv/dt, in which C is I/O pin capacitance and dv/dt is the slew rate.

Figure 4: LVTTL/LVCMOS Input Standard Voltage Diagram





Figure 5: Schmitt Trigger Input Standard Voltage Diagram



I/O Standards Specifications

Tables in this section list input voltage (V_{IH} and V_{IL}), output voltage (V_{OH} and V_{OL}), and current drive characteristics (I_{OH} and I_{OL}) for various I/O standards supported by MAX 10 devices.

For minimum voltage values, use the minimum V_{CCIO} values. For maximum voltage values, use the maximum V_{CCIO} values.

You must perform timing closure analysis to determine the maximum achievable frequency for general purpose I/O standards.

Single-Ended I/O Standards Specifications

Table 19: Single-Ended I/O Standards Specifications for MAX 10 Devices—Preliminary

To meet the I_{OL} and I_{OH} specifications, you must set the current strength settings accordingly. For example, to meet the 3.3-V LVTTL specification (4 mA), you should set the current strength settings to 4 mA. Setting at lower current strength may not meet the I_{OL} and I_{OH} specifications in the datasheet.

I/O Standard	V_{CCIO} (V)			V_{IL} (V)		V_{IH} (V)		V_{OL} (V)	V_{OH} (V)	I_{OL} (mA)	I_{OH} (mA)
	Min	Typ	Max	Min	Max	Min	Max	Max	Min		
3.3 V LVTTL	3.135	3.3	3.465	-0.3	0.8	1.7	3.6	0.45	2.4	4	-4
3.3 V LVCMOS	3.135	3.3	3.465	-0.3	0.8	1.7	3.6	0.2	$V_{CCIO} - 0.2$	2	-2
3.0 V LVTTL	2.85	3	3.15	-0.3	0.8	1.7	$V_{CCIO} + 0.3$	0.45	2.4	4	-4
3.0 V LVCMOS	2.85	3	3.15	-0.3	0.8	1.7	$V_{CCIO} + 0.3$	0.2	$V_{CCIO} - 0.2$	0.1	-0.1
2.5 V LVTTL and LVCMOS	2.375	2.5	2.625	-0.3	0.7	1.7	$V_{CCIO} + 0.3$	0.4	2	1	-1
1.8 V LVTTL and LVCMOS	1.71	1.8	1.89	-0.3	$0.35 \times V_{CCIO}$	$0.65 \times V_{CCIO}$	2.25	0.45	$V_{CCIO} - 0.45$	2	-2
1.5 V LVCMOS	1.425	1.5	1.575	-0.3	$0.35 \times V_{CCIO}$	$0.65 \times V_{CCIO}$	$V_{CCIO} + 0.3$	$0.25 \times V_{CCIO}$	$0.75 \times V_{CCIO}$	2	-2
1.2 V LVCMOS	1.14	1.2	1.26	-0.3	$0.35 \times V_{CCIO}$	$0.65 \times V_{CCIO}$	$V_{CCIO} + 0.3$	$0.25 \times V_{CCIO}$	$0.75 \times V_{CCIO}$	2	-2
3.3 V Schmitt Trigger	3.135	3.3	3.465	-0.3	0.8	1.7	$V_{CCIO} + 0.3$	—	—	—	—
2.5 V Schmitt Trigger	2.375	2.5	2.625	-0.3	0.7	1.7	$V_{CCIO} + 0.3$	—	—	—	—
1.8 V Schmitt Trigger	1.71	1.8	1.89	-0.3	$0.35 \times V_{CCIO}$	$0.65 \times V_{CCIO}$	$V_{CCIO} + 0.3$	—	—	—	—
1.5 V Schmitt Trigger	1.425	1.5	1.575	-0.3	$0.35 \times V_{CCIO}$	$0.65 \times V_{CCIO}$	$V_{CCIO} + 0.3$	—	—	—	—

I/O Standard	V _{CCIO} (V)			V _{IL} (V)		V _{IH} (V)		V _{OL} (V)	V _{OH} (V)	I _{OL} (mA)	I _{OH} (mA)
	Min	Typ	Max	Min	Max	Min	Max	Max	Min		
3.0 V PCI	2.85	3	3.15	—	0.3 × V _{CCIO}	0.5 × V _{CCIO}	V _{CCIO} + 0.3	0.1 × V _{CCIO}	0.9 × V _{CCIO}	1.5	-0.5

Single-Ended SSTL, HSTL, and HSUL I/O Reference Voltage Specifications

Table 20: Single-Ended SSTL, HSTL, and HSUL I/O Reference Voltage Specifications for MAX 10 Devices—Preliminary

I/O Standard	V _{CCIO} (V)			V _{REF} (V)			V _{TT} (V) ⁽¹⁴⁾		
	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max
SSTL-2 Class I, II	2.375	2.5	2.625	1.19	1.25	1.31	V _{REF} - 0.04	V _{REF}	V _{REF} + 0.04
SSTL-18 Class I, II	1.7	1.8	1.9	0.833	0.9	0.969	V _{REF} - 0.04	V _{REF}	V _{REF} + 0.04
SSTL-15 Class I, II	1.425	1.5	1.575	0.49 × V _{CCIO}	0.5 × V _{CCIO}	0.51 × V _{CCIO}	0.49 × V _{CCIO}	0.5 × V _{CCIO}	0.51 × V _{CCIO}
SSTL-135 Class I, II	1.283	1.35	1.45	0.49 × V _{CCIO}	0.5 × V _{CCIO}	0.51 × V _{CCIO}	0.49 × V _{CCIO}	0.5 × V _{CCIO}	0.51 × V _{CCIO}
HSTL-18 Class I, II	1.71	1.8	1.89	0.85	0.9	0.95	0.85	0.9	0.95
HSTL-15 Class I, II	1.425	1.5	1.575	0.71	0.75	0.79	0.71	0.75	0.79
HSTL-12 Class I, II	1.14	1.2	1.26	0.48 × V _{CCIO} ⁽¹⁵⁾	0.5 × V _{CCIO} ⁽¹⁵⁾	0.52 × V _{CCIO} ⁽¹⁵⁾	—	0.5 × V _{CCIO}	—
				0.47 × V _{CCIO} ⁽¹⁶⁾	0.5 × V _{CCIO} ⁽¹⁶⁾	0.53 × V _{CCIO} ⁽¹⁶⁾			

⁽¹⁴⁾ V_{TT} of transmitting device must track V_{REF} of the receiving device.

⁽¹⁵⁾ Value shown refers to DC input reference voltage, V_{REF(DC)}.

⁽¹⁶⁾ Value shown refers to AC input reference voltage, V_{REF(AC)}.

I/O Standard	V _{CCIO} (V)			V _{REF} (V)			V _{TT} (V) ⁽¹⁴⁾		
	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max
HSUL-12	1.14	1.2	1.3	0.49 × V _{CCIO}	0.5 × V _{CCIO}	0.51 × V _{CCIO}	—	—	—

Single-Ended SSTL, HSTL, and HSUL I/O Standards Signal Specifications

Table 21: Single-Ended SSTL, HSTL, and HSUL I/O Standards Signal Specifications for MAX 10 Devices—Preliminary

To meet the I_{OL} and I_{OH} specifications, you must set the current strength settings accordingly. For example, to meet the SSTL-15 Class I specification (8 mA), you should set the current strength settings to 8 mA. Setting at lower current strength may not meet the I_{OL} and I_{OH} specifications in the datasheet.

I/O Standard	V _{IL(DC)} (V)		V _{IH(DC)} (V)		V _{IL(AC)} (V)		V _{IH(AC)} (V)		V _{OL} (V)	V _{OH} (V)	I _{OL} (mA)	I _{OH} (mA)
	Min	Max	Min	Max	Min	Max	Min	Max	Max	Min		
SSTL-2 Class I	—	V _{REF} – 0.18	V _{REF} + 0.18	—	—	V _{REF} – 0.31	V _{REF} + 0.31	—	V _{TT} – 0.57	V _{TT} + 0.57	8.1	-8.1
SSTL-2 Class II	—	V _{REF} – 0.18	V _{REF} + 0.18	—	—	V _{REF} – 0.31	V _{REF} + 0.31	—	V _{TT} – 0.76	V _{TT} + 0.76	16.4	-16.4
SSTL-18 Class I	—	V _{REF} – 0.125	V _{REF} + 0.125	—	—	V _{REF} – 0.25	V _{REF} + 0.25	—	V _{TT} – 0.475	V _{TT} + 0.475	6.7	-6.7
SSTL-18 Class II	—	V _{REF} – 0.125	V _{REF} + 0.125	—	—	V _{REF} – 0.25	V _{REF} + 0.25	—	0.28	V _{CCIO} – 0.28	13.4	-13.4
SSTL-15 Class I	—	V _{REF} – 0.1	V _{REF} + 0.1	—	—	V _{REF} – 0.175	V _{REF} + 0.175	—	0.2 × V _{CCIO}	0.8 × V _{CCIO}	8	-8
SSTL-15 Class II	—	V _{REF} – 0.1	V _{REF} + 0.1	—	—	V _{REF} – 0.175	V _{REF} + 0.175	—	0.2 × V _{CCIO}	0.8 × V _{CCIO}	16	-16
SSTL-135	—	V _{REF} – 0.09	V _{REF} + 0.09	—	—	V _{REF} – 0.16	V _{REF} + 0.16	—	0.2 × V _{CCIO}	0.8 × V _{CCIO}	—	—
HSTL-18 Class I	—	V _{REF} – 0.1	V _{REF} + 0.1	—	—	V _{REF} – 0.2	V _{REF} + 0.2	—	0.4	V _{CCIO} – 0.4	8	-8

⁽¹⁴⁾ V_{TT} of transmitting device must track V_{REF} of the receiving device.

I/O Standard	V _{IL(DC)} (V)		V _{IH(DC)} (V)		V _{IL(AC)} (V)		V _{IH(AC)} (V)		V _{OL} (V)	V _{OH} (V)	I _{OL} (mA)	I _{OH} (mA)
	Min	Max	Min	Max	Min	Max	Min	Max	Max	Min		
HSTL-18 Class II	—	V _{REF} - 0.1	V _{REF} + 0.1	—	—	V _{REF} - 0.2	V _{REF} + 0.2	—	0.4	V _{CCIO} - 0.4	16	-16
HSTL-15 Class I	—	V _{REF} - 0.1	V _{REF} + 0.1	—	—	V _{REF} - 0.2	V _{REF} + 0.2	—	0.4	V _{CCIO} - 0.4	8	-8
HSTL-15 Class II	—	V _{REF} - 0.1	V _{REF} + 0.1	—	—	V _{REF} - 0.2	V _{REF} + 0.2	—	0.4	V _{CCIO} - 0.4	16	-16
HSTL-12 Class I	-0.15	V _{REF} - 0.08	V _{REF} + 0.08	V _{CCIO} + 0.15	-0.24	V _{REF} - 0.15	V _{REF} + 0.15	V _{CCIO} + 0.24	0.25 × V _{CCIO}	0.75 × V _{CCIO}	8	-8
HSTL-12 Class II	-0.15	V _{REF} - 0.08	V _{REF} + 0.08	V _{CCIO} + 0.15	-0.24	V _{REF} - 0.15	V _{REF} + 0.15	V _{CCIO} + 0.24	0.25 × V _{CCIO}	0.75 × V _{CCIO}	14	-14
HSUL-12	—	V _{REF} - 0.13	V _{REF} + 0.13	—	—	V _{REF} - 0.22	V _{REF} + 0.22	—	0.1 × V _{CCIO}	0.9 × V _{CCIO}	—	—

Differential SSTL I/O Standards Specifications

Differential SSTL requires a V_{REF} input.

Table 22: Differential SSTL I/O Standards Specifications for MAX 10 Devices—Preliminary

I/O Standard	V _{CCIO} (V)			V _{Swing(DC)} (V)		V _{X(AC)} (V)			V _{Swing(AC)} (V)	
	Min	Typ	Max	Min	Max ⁽¹⁷⁾	Min	Typ	Max	Min	Max
SSTL-2 Class I, II	2.375	2.5	2.625	0.36	V _{CCIO}	V _{CCIO} /2 - 0.2	—	V _{CCIO} /2 + 0.2	0.7	V _{CCIO}
SSTL-18 Class I, II	1.7	1.8	1.9	0.25	V _{CCIO}	V _{CCIO} /2 - 0.175	—	V _{CCIO} /2 + 0.175	0.5	V _{CCIO}
SSTL-15 Class I, II	1.425	1.5	1.575	0.2	—	V _{CCIO} /2 - 0.15	—	V _{CCIO} /2 + 0.15	2(V _{IH(AC)} - V _{REF})	2(V _{IL(AC)} - V _{REF})

⁽¹⁷⁾ The maximum value for V_{SWING(DC)} is not defined. However, each single-ended signal needs to be within the respective single-ended limits (V_{IH(DC)} and V_{IL(DC)}).

I/O Standard	V _{CCIO} (V)			V _{Swing(DC)} (V)		V _{X(AC)} (V)			V _{Swing(AC)} (V)	
	Min	Typ	Max	Min	Max ⁽¹⁷⁾	Min	Typ	Max	Min	Max
SSTL-135	1.283	1.35	1.45	0.18	—	V _{REF} – 0.135	0.5 × V _{CCIO}	V _{REF} + 0.135	2(V _{IH(AC)} – V _{REF})	2(V _{IL(AC)} – V _{REF})

Differential HSTL and HSUL I/O Standards Specifications

Differential HSTL requires a V_{REF} input.

Table 23: Differential HSTL and HSUL I/O Standards Specifications for MAX 10 Devices—Preliminary

I/O Standard	V _{CCIO} (V)			V _{DIF(DC)} (V)		V _{X(AC)} (V)			V _{CM(DC)} (V)			V _{DIF(AC)} (V)
	Min	Typ	Max	Min	Max	Min	Typ	Max	Min	Typ	Max	Min
HSTL-18 Class I, II	1.71	1.8	1.89	0.2	—	0.85	—	0.95	0.85	—	0.95	0.4
HSTL-15 Class I, II	1.425	1.5	1.575	0.2	—	0.71	—	0.79	0.71	—	0.79	0.4
HSTL-12 Class I, II	1.14	1.2	1.26	0.16	V _{CCIO}	0.48 × V _{CCIO}	0.5 × V _{CCIO}	0.52 × V _{CCIO}	0.48 × V _{CCIO}	0.5 × V _{CCIO}	0.52 × V _{CCIO}	0.3
HSUL-12	1.14	1.2	1.3	0.26	—	0.5 × V _{CCIO} – 0.12	0.5 × V _{CCIO}	0.5 × V _{CCIO} + 0.12	0.4 × V _{CCIO}	0.5 × V _{CCIO}	0.6 × V _{CCIO}	0.44

⁽¹⁷⁾ The maximum value for V_{SWING(DC)} is not defined. However, each single-ended signal needs to be within the respective single-ended limits (V_{IH(DC)} and V_{IL(DC)}).

Differential I/O Standards Specifications

Table 24: Differential I/O Standards Specifications for MAX 10 Devices—Preliminary

I/O Standard	V _{CCIO} (V)			V _{ID} (mV)		V _{ICM} (V) ⁽¹⁸⁾			V _{OD} (mV) ⁽¹⁹⁾⁽²⁰⁾			V _{OS} (V) ⁽¹⁹⁾		
	Min	Typ	Max	Min	Max	Min	Condition	Max	Min	Typ	Max	Min	Typ	Max
LVPECL ⁽²¹⁾	2.375	2.5	2.625	100	—	0.05	D _{MAX} ≤ 500 Mbps	1.8	—	—	—	—	—	—
						0.55	500 Mbps ≤ D _{MAX} ≤ 700 Mbps	1.8						
						1.05	D _{MAX} > 700 Mbps	1.55						
LVDS	2.375	2.5	2.625	100	—	0.05	D _{MAX} ≤ 500 Mbps	1.8	247	—	600	1.125	1.25	1.375
						0.55	500 Mbps ≤ D _{MAX} ≤ 700 Mbps	1.8						
						1.05	D _{MAX} > 700 Mbps	1.55						
BLVDS ⁽²²⁾ ⁽²³⁾	2.375	2.5	2.625	100	—	—	—	—	—	—	—	—	—	—
mini-LVDS ⁽²⁴⁾	2.375	2.5	2.625	—	—	—	—	—	300	—	600	1	1.2	1.4
RSDS ⁽²⁴⁾	2.375	2.5	2.625	—	—	—	—	—	100	200	600	0.5	1.2	1.5
PPDS (Row I/Os) ⁽²⁴⁾	2.375	2.5	2.625	—	—	—	—	—	100	200	600	0.5	1.2	1.4

⁽¹⁸⁾ V_{IN} range: 0 V ≤ V_{IN} ≤ 1.85 V.

⁽¹⁹⁾ R_L range: 90 ≤ R_L ≤ 110 Ω.

⁽²⁰⁾ Low V_{OD} setting is only supported for RSDS standard.

⁽²¹⁾ LVPECL input standard is only supported at clock input. Output standard is not supported.

⁽²²⁾ No fixed V_{IN}, V_{OD}, and V_{OS} specifications for Bus LVDS (BLVDS). They are dependent on the system topology.

⁽²³⁾ BLVDS TX is not supported in single supply devices.

⁽²⁴⁾ Mini-LVDS, RSDS, and Point-to-Point Differential Signaling (PPDS) standards are only supported at the output pins for MAX 10 devices.

I/O Standard	V _{CCIO} (V)			V _{ID} (mV)		V _{ICM} (V) ⁽¹⁸⁾			V _{OD} (mV) ⁽¹⁹⁾⁽²⁰⁾			V _{OS} (V) ⁽¹⁹⁾				
	Min	Typ	Max	Min	Max	Min	Condition	Max	Min	Typ	Max	Min	Typ	Max		
TMDS ⁽²⁵⁾	2.375	2.5	2.625	100	—	0.05	D _{MAX} ≤ 500 Mbps	1.8	—	—	—	—	—	—		
						0.55	500 Mbps ≤ D _{MAX} ≤ 700 Mbps	1.8								
						1.05	D _{MAX} > 700 Mbps	1.55								
Sub-LVDS ⁽²⁶⁾	1.71	1.8	1.89	100	—	0.55	—	1.25	(27)			0.8	0.9	1		
SLVS	2.375	2.5	2.625	100	—	0.05	—	1.1				(28)				
HiSpi	2.375	2.5	2.625	100	—	0.05	D _{MAX} ≤ 500 Mbps	1.8	—	—	—	—	—	—		
						0.55	500 Mbps ≤ D _{MAX} ≤ 700 Mbps	1.8								
						1.05	D _{MAX} > 700 Mbps	1.55								

Related Information

[MAX 10 High-Speed LVDS I/O User Guide](#)

Provides the list of I/O standards supported in single supply and dual supply devices.

Switching Characteristics

This section provides the performance characteristics of MAX 10 core and periphery blocks.

⁽¹⁸⁾ V_{IN} range: 0 V ≤ V_{IN} ≤ 1.85 V.

⁽¹⁹⁾ R_L range: 90 ≤ R_L ≤ 110 Ω.

⁽²⁰⁾ Low V_{OD} setting is only supported for RS232 standard.

⁽²⁵⁾ Supported with requirement of an external level shift

⁽²⁶⁾ Sub-LVDS input buffer is using 2.5 V differential buffer.

⁽²⁷⁾ Differential output depends on the values of the external termination resistors.

⁽²⁸⁾ Differential output offset voltage depends on the values of the external termination resistors.

Core Performance Specifications

Clock Tree Specifications

Table 25: Clock Tree Specifications for MAX 10 Devices—Preliminary

Device	Performance					Unit
	-I6	-C7	-I7	-A7	-C8	
10M02	450	416	416	382	402	MHz
10M04	450	416	416	382	402	MHz
10M08	450	416	416	382	402	MHz
10M16	450	416	416	382	402	MHz
10M25	450	416	416	382	402	MHz
10M40	450	416	416	382	402	MHz
10M50	450	416	416	382	402	MHz

PLL Specifications

Table 26: PLL Specifications for MAX 10 Devices—Preliminary

V_{CCD_PLL} should always be connected to V_{CCINT} through decoupling capacitor and ferrite bead.

Symbol	Parameter	Condition	Min	Typ	Max	Unit
$f_{IN}^{(29)}$	Input clock frequency	—	5	—	472.5	MHz
f_{INPFD}	Phase frequency detector (PFD) input frequency	—	5	—	325	MHz
$f_{VCO}^{(30)}$	PLL internal voltage-controlled oscillator (VCO) operating range	—	600	—	1300	MHz

⁽²⁹⁾ This parameter is limited in the Quartus II software by the I/O maximum frequency. The maximum I/O frequency is different for each I/O standard.

⁽³⁰⁾ The VCO frequency reported by the Quartus II software in the PLL summary section of the compilation report takes into consideration the VCO post-scale counter κ value. Therefore, if the counter κ has a value of 2, the frequency reported can be lower than the f_{VCO} specification.

Symbol	Parameter	Condition	Min	Typ	Max	Unit
f_{INDUTY}	Input clock duty cycle	—	40	—	60	%
$t_{INJITTER_CCJ}^{(31)}$	Input clock cycle-to-cycle jitter	$F_{INPFD} \geq 100$ MHz	—	—	0.15	UI
		$F_{INPFD} < 100$ MHz	—	—	750	ps
$f_{OUT_EXT}^{(29)}$	PLL output frequency for external clock output	—	—	—	472.5	MHz
f_{OUT}	PLL output frequency to global clock	-6 speed grade	—	—	472.5	MHz
		-7 speed grade	—	—	450	MHz
		-8 speed grade	—	—	402.5	MHz
$t_{OUTDUTY}$	Duty cycle for external clock output	Duty cycle set to 50%	45	50	55	%
t_{LOCK}	Time required to lock from end of device configuration	—	—	—	1	ms
t_{DLOCK}	Time required to lock dynamically	After switchover, reconfiguring any non-post-scale counters or delays, or when <code>areset</code> is deasserted	—	—	1	ms
$t_{OUTJITTER_PERIOD_IO}^{(32)}$	Regular I/O period jitter	$F_{OUT} \geq 100$ MHz	—	—	650	ps
		$F_{OUT} < 100$ MHz	—	—	75	mUI
$t_{OUTJITTER_CCJ_IO}^{(32)}$	Regular I/O cycle-to-cycle jitter	$F_{OUT} \geq 100$ MHz	—	—	650	ps
		$F_{OUT} < 100$ MHz	—	—	75	mUI
t_{PLL_PSERR}	Accuracy of PLL phase shift	—	—	—	± 50	ps
t_{ARESET}	Minimum pulse width on <code>areset</code> signal.	—	10	—	—	ns

⁽³¹⁾ A high input jitter directly affects the PLL output jitter. To have low PLL output clock jitter, you must provide a clean clock source, which is less than 200 ps.

⁽³²⁾ Peak-to-peak jitter with a probability level of 10^{-12} (14 sigma, 99.9999999974404% confidence level). The output jitter specification applies to the intrinsic jitter of the PLL, when an input jitter of 30 ps is applied.

Symbol	Parameter	Condition	Min	Typ	Max	Unit
$t_{CONFIGPLL}$	Time required to reconfigure scan chains for PLLs	—	—	3.5 ⁽³³⁾	—	SCANCLK cycles
$f_{SCANCLK}$	scanclk frequency	—	—	—	100	MHz

Table 27: PLL Specifications for MAX 10 Single Supply Devices—Preliminary

For V36 package, the PLL specification is based on single supply devices.

Symbol	Parameter	Condition	Max	Unit
$t_{OUTJITTER_PERIOD_DEDCLK}^{(32)}$	Dedicated clock output period jitter	$F_{OUT} \geq 100$ MHz	660	ps
		$F_{OUT} < 100$ MHz	66	mUI
$t_{OUTJITTER_CCJ_DEDCLK}^{(32)}$	Dedicated clock output cycle-to-cycle jitter	$F_{OUT} \geq 100$ MHz	660	ps
		$F_{OUT} < 100$ MHz	66	mUI

Table 28: PLL Specifications for MAX 10 Dual Supply Devices—Preliminary

Symbol	Parameter	Condition	Max	Unit
$t_{OUTJITTER_PERIOD_DEDCLK}^{(32)}$	Dedicated clock output period jitter	$F_{OUT} \geq 100$ MHz	300	ps
		$F_{OUT} < 100$ MHz	30	mUI
$t_{OUTJITTER_CCJ_DEDCLK}^{(32)}$	Dedicated clock output cycle-to-cycle jitter	$F_{OUT} \geq 100$ MHz	300	ps
		$F_{OUT} < 100$ MHz	30	mUI

⁽³³⁾ With 100 MHz scanclk frequency.

Embedded Multiplier Specifications

Table 29: Embedded Multiplier Specifications for MAX 10 Devices—Preliminary

Mode	Number of Multipliers	Power Supply Mode	Performance			Unit
			-I6	-C7, -I7, -A7	-C8	
9 × 9-bit multiplier	1	Single supply mode	198	183	160	MHz
		Dual supply mode	234	212	180	MHz
18 × 18-bit multiplier	1	Single supply mode	198	183	160	MHz
		Dual supply mode	234	212	180	MHz

Memory Block Performance Specifications

Table 30: Memory Block Performance Specifications for MAX 10 Devices—Preliminary

Memory	Mode	Resources Used		Power Supply Mode	Performance			Unit
		LEs	M9K Memory		-I6	-C7, -I7, -A7	-C8	
M9K Block	FIFO 256 × 36	47	1	Single supply mode	232	219	204	MHz
				Dual supply mode	284	260	238	MHz
	Single-port 256 × 36	0	1	Single supply mode	232	219	204	MHz
				Dual supply mode	284	260	238	MHz
	Simple dual-port 256 × 36 CLK	0	1	Single supply mode	232	219	204	MHz
				Dual supply mode	284	260	238	MHz
	True dual port 512 × 18 single CLK	0	1	Single supply mode	232	219	204	MHz
				Dual supply mode	284	260	238	MHz

Internal Oscillator Specifications

Table 31: Internal Oscillator Frequencies for MAX 10 Devices—Preliminary

You can access to the internal oscillator frequencies in this table. The duty cycle of internal oscillator is approximately 45%–55%.

Device	Operating Frequency	Unit
10M02		
10M04		
10M08	55 – 116	MHz
10M16		
10M25		
10M40	35 – 77	MHz
10M50		

UFM Performance Specifications

Table 32: UFM Performance Specifications for MAX 10 Devices—Preliminary

Block	Mode	Interface	Performance	Unit
			-I6, -C7, -I7, -A7, -C8	
UFM	Avalon-MM slave	Parallel	116	MHz
		Serial	7.25	MHz

ADC Performance Specifications

Single Supply Devices ADC Performance Specifications

Table 33: ADC Performance Specifications for MAX 10 Single Supply Devices—Preliminary

Parameter	Symbol	Condition	Min	Typ	Max	Unit
ADC resolution	—	—	—	—	12	bits

Parameter	Symbol	Condition	Min	Typ	Max	Unit
ADC supply voltage	V _{CC_ONE}	—	2.85	3.0/3.3	3.465	V
External reference voltage	V _{REF}	—	V _{CC_ONE} − 0.5	—	V _{CC_ONE}	V
Sampling rate	F _S	Accumulative sampling rate	—	—	1000	kSPS
Input frequency	F _{IN}	—	—	—	50	kHz
Operating ambient temperature range	T _A	—	-40	25	125	°C
Analog input voltage	V _{IN}	Prescalar disabled	0	—	V _{REF}	V
		Prescalar enabled	0	—	3.6	V
Input resistance	R _{IN}	—	—	(34)	—	kΩ
Input capacitance	C _{IN}	Dedicated analog input	—	(34)	—	pF
		Dual function pin	—	(34)	—	pF
DC Accuracy	Offset error and drift	E _{offset}	Prescalar disabled	-0.2	—	%FS
			Prescalar enabled	-0.5	—	%FS
	Gain error and drift	E _{gain}	Prescalar disabled	-0.5	—	%FS
			Prescalar enabled	-0.75	—	%FS
AC Accuracy	Differential non linearity	DNL	No missing codes	-0.9	—	LSB
	Integral non linearity	INL	—	-2	—	LSB
	Total harmonic distortion	THD	F _{IN} = 50 kHz, F _S = 1 MHz, PLL	-65	—	—
	Signal-to-noise ratio	SNR	F _{IN} = 50 kHz, F _S = 1 MHz, PLL	54	—	—
	Signal-to-noise and distortion	SINAD	F _{IN} = 50 kHz, F _S = 1 MHz, PLL	53	—	—

⁽³⁴⁾ Refer to the MAX 10 Analog-to-Digital Converter User Guide for the RC equation.

Parameter		Symbol	Condition	Min	Typ	Max	Unit
On-Chip Temperature Sensor	Temperature sampling rate	T _S	—	—	—	50	kSPS
	Absolute accuracy	—	-40 to 125°C	—	—	±10	°C
Conversion Rate ⁽³⁵⁾	Conversion time	—	Single measurement	—	—	1	Cycle
			Continuous measurement	—	—	1	Cycle
			Temperature measurement	—	—	1	Cycle

Related Information**MAX 10 Analog-to-Digital Converter User Guide**

Provides more information about the conversion rate and RC equation.

Dual Supply Devices ADC Performance Specifications**Table 34: ADC Performance Specifications for MAX 10 Dual Supply Devices—Preliminary**

Parameter	Symbol	Condition	Min	Typ	Max	Unit
ADC resolution	—	—	—	—	12	bits
Analog supply voltage	V _{CCA_ADC}	—	2.375	2.5	2.625	V
Digital supply voltage	V _{CCINT}	—	1.14	1.2	1.26	V
External reference voltage	V _{REF}	—	V _{CCA_ADC} – 0.5	—	V _{CCA_ADC}	V
Sampling rate	F _S	Accumulative sampling rate	—	—	1000	kSPS
Input frequency	F _{IN}	—	—	—	50	kHz
Operating ambient temperature range	T _A	—	-40	25	125	°C

⁽³⁵⁾ For more detailed description, refer to Timing section in the MAX 10 Analog-to-Digital Converter User Guide.

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Analog input voltage	V_{IN}	Prescalar disabled	0	—	V_{REF}	V
		Prescalar enabled	0	—	3	V
Analog supply current (DC)	I_{ACC_ADC}	Average current	—	275	450	μA
Digital supply current (DC)	I_{CCINT}	Average current	—	65	150	μA
Input resistance	R_{IN}	—	—	(36)	—	$k\Omega$
Input capacitance	C_{IN}	Dedicated analog input	—	(36)	—	pF
		Dual function pin	—	(36)	—	pF
DC Accuracy	Offset error and drift	E_{offset}	Prescalar disabled	-0.2	—	%FS
			Prescalar enabled	-0.5	—	%FS
	Gain error and drift	E_{gain}	Prescalar disabled	-0.5	—	%FS
			Prescalar enabled	-0.75	—	%FS
	DNL	No missing codes	-0.9	—	0.9	LSB
AC Accuracy	Integral non linearity	INL	—	-2	—	LSB
	Total harmonic distortion	THD	$F_{IN} = 50 \text{ kHz}, F_S = 1 \text{ MHz, PLL}$	-70 ⁽³⁷⁾	—	—
	Signal-to-noise ratio	SNR	$F_{IN} = 50 \text{ kHz}, F_S = 1 \text{ MHz, PLL}$	62 ⁽³⁸⁾	—	—
	Signal-to-noise and distortion	SINAD	$F_{IN} = 50 \text{ kHz}, F_S = 1 \text{ MHz, PLL}$	61.5 ⁽³⁹⁾	—	—

⁽³⁶⁾ Refer to the MAX 10 Analog-to-Digital Converter User Guide for the RC equation.

⁽³⁷⁾ Total harmonic distortion is -65 dB for dual function pin.

⁽³⁸⁾ Signal-to-noise ratio is 54 dB for dual function pin.

⁽³⁹⁾ Signal-to-noise and distortion is 53 dB for dual function pin.

Parameter		Symbol	Condition	Min	Typ	Max	Unit
On-Chip Temperature Sensor	Temperature sampling rate	T _S	—	—	—	50	kSPS
	Absolute accuracy	—	-40 to 125°C, with 64 samples averaging	—	—	±5	°C
Conversion Rate ⁽⁴⁰⁾	Conversion time	—	Single measurement	—	—	1	Cycle
			Continuous measurement	—	—	1	Cycle
			Temperature measurement	—	—	1	Cycle

Related Information**[MAX 10 Analog-to-Digital Converter User Guide](#)**

Provides more information about the conversion rate and RC equation.

Periphery Performance Specifications

This section describes the periphery performance, high-speed I/O, and external memory interface.

Actual achievable frequency depends on design and system specific factors. Ensure proper timing closure in your design and perform HSPICE/IBIS simulations based on your specific design and system setup to determine the maximum achievable frequency in your system.

High-Speed I/O Specifications

For more information about the high-speed and low-speed I/O performance pins, refer to the respective device pin-out files.

⁽⁴⁰⁾ For more detailed description, refer to Timing section in the MAX 10 Analog-to-Digital Converter User Guide.

True PPDS and Emulated PPDS_E_3R Transmitter Timing Specifications

Table 35: True PPDS and Emulated PPDS_E_3R Transmitter Timing Specifications for MAX 10 Dual Supply Devices—Preliminary

True PPDS transmitter is only supported at bottom I/O bank. Emulated PPDS transmitter is supported at the output pin of all I/O banks.

Symbol	Parameter	Mode	-I6, -C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
f_{HSCLK}	Input clock frequency (high-speed I/O performance pin)	×10	5	—	155	5	—	150	5	—	155	MHz
		×8	5	—	155	5	—	150	5	—	155	MHz
		×7	5	—	155	5	—	150	5	—	155	MHz
		×4	5	—	155	5	—	150	5	—	155	MHz
		×2	5	—	155	5	—	150	5	—	155	MHz
		×1	5	—	310	5	—	300	5	—	310	MHz
f_{HSIODR}	Data rate (high-speed I/O performance pin)	×10	100	—	310	100	—	300	100	—	310	Mbps
		×8	80	—	310	80	—	300	80	—	310	Mbps
		×7	70	—	310	70	—	300	70	—	310	Mbps
		×4	40	—	310	40	—	300	40	—	310	Mbps
		×2	20	—	310	20	—	300	20	—	310	Mbps
		×1	10	—	310	10	—	300	10	—	310	Mbps
f_{HSCLK}	Input clock frequency (low-speed I/O performance pin)	×10	5	—	150	5	—	145	5	—	150	MHz
		×8	5	—	150	5	—	145	5	—	150	MHz
		×7	5	—	150	5	—	145	5	—	150	MHz
		×4	5	—	150	5	—	145	5	—	150	MHz
		×2	5	—	150	5	—	145	5	—	150	MHz
		×1	5	—	300	5	—	290	5	—	300	MHz

Symbol	Parameter	Mode	-I6, -C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
HSIODR	Data rate (low-speed I/O performance pin)	×10	100	—	300	100	—	290	100	—	300	Mbps
		×8	80	—	300	80	—	290	80	—	300	Mbps
		×7	70	—	300	70	—	290	70	—	300	Mbps
		×4	40	—	300	40	—	290	40	—	300	Mbps
		×2	20	—	300	20	—	290	20	—	300	Mbps
		×1	10	—	300	10	—	290	10	—	300	Mbps
t _{DUTY}	Duty cycle on transmitter output clock	—	45	—	55	45	—	55	45	—	55	%
TCCS ⁽⁴¹⁾	Transmitter channel-to-channel skew	—	—	—	340	—	—	340	—	—	340	ps
t _{x jitter}	Output jitter	—	—	—	500	—	—	500	—	—	500	ps
t _{RISE}	Rise time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{FALL}	Fall time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{LOCK}	Time required for the PLL to lock from the end of device configuration.	—	—	—	1	—	—	1	—	—	1	ms

⁽⁴¹⁾ TCCS specifications apply to I/O banks from the same side only.

True RSDS and Emulated RSDS_E_3R Transmitter Timing Specifications

Table 36: True RSDS and Emulated RSDS_E_3R Transmitter Timing Specifications for MAX 10 Dual Supply Devices—Preliminary

True RSDS transmitter is only supported at bottom I/O bank. Emulated RSDS transmitter is supported at the output pin of all I/O banks.

Symbol	Parameter	Mode	-I6, -C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
f_{HSCLK}	Input clock frequency (high-speed I/O performance pin)	×10	5	—	155	5	—	150	5	—	155	MHz
		×8	5	—	155	5	—	150	5	—	155	MHz
		×7	5	—	155	5	—	150	5	—	155	MHz
		×4	5	—	155	5	—	150	5	—	155	MHz
		×2	5	—	155	5	—	150	5	—	155	MHz
		×1	5	—	310	5	—	300	5	—	310	MHz
f_{HSODR}	Data rate (high-speed I/O performance pin)	×10	100	—	310	100	—	300	100	—	310	Mbps
		×8	80	—	310	80	—	300	80	—	310	Mbps
		×7	70	—	310	70	—	300	70	—	310	Mbps
		×4	40	—	310	40	—	300	40	—	310	Mbps
		×2	20	—	310	20	—	300	20	—	310	Mbps
		×1	10	—	310	10	—	300	10	—	310	Mbps
f_{HSCLK}	Input clock frequency (low-speed I/O performance pin)	×10	5	—	150	5	—	145	5	—	150	MHz
		×8	5	—	150	5	—	145	5	—	150	MHz
		×7	5	—	150	5	—	145	5	—	150	MHz
		×4	5	—	150	5	—	145	5	—	150	MHz
		×2	5	—	150	5	—	145	5	—	150	MHz
		×1	5	—	300	5	—	290	5	—	300	MHz

Symbol	Parameter	Mode	-I6, -C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
HSIODR	Data rate (low-speed I/O performance pin)	×10	100	—	300	100	—	290	100	—	300	Mbps
		×8	80	—	300	80	—	290	80	—	300	Mbps
		×7	70	—	300	70	—	290	70	—	300	Mbps
		×4	40	—	300	40	—	290	40	—	300	Mbps
		×2	20	—	300	20	—	290	20	—	300	Mbps
		×1	10	—	300	10	—	290	10	—	300	Mbps
t _{DUTY}	Duty cycle on transmitter output clock	—	45	—	55	45	—	55	45	—	55	%
TCCS ⁽⁴²⁾	Transmitter channel-to-channel skew	—	—	—	340	—	—	340	—	—	340	ps
t _{x Jitter}	Output jitter (for multi supply devices)	—	—	—	500	—	—	500	—	—	500	ps
t _{RISE}	Rise time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{FALL}	Fall time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{LOCK}	Time required for the PLL to lock from the end of device configuration.	—	—	—	1	—	—	1	—	—	1	ms

⁽⁴²⁾ TCCS specifications apply to I/O banks from the same side only.

Emulated RSDS_E_1R Transmitter Timing Specifications

Table 37: Emulated RSDS_E_1R Transmitter Timing Specifications for MAX 10 Dual Supply Devices—Preliminary

Emulated RSDS_E_1R transmitter is supported at the output pin of all I/O banks.

Symbol	Parameter	Mode	-I6, -C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
f_{HSCLK}	Input clock frequency (high-speed I/O performance pin)	×10	5	—	85	5	—	85	5	—	85	MHz
		×8	5	—	85	5	—	85	5	—	85	MHz
		×7	5	—	85	5	—	85	5	—	85	MHz
		×4	5	—	85	5	—	85	5	—	85	MHz
		×2	5	—	85	5	—	85	5	—	85	MHz
		×1	5	—	170	5	—	170	5	—	170	MHz
$HSIODR$	Data rate (high-speed I/O performance pin)	×10	100	—	170	100	—	170	100	—	170	Mbps
		×8	80	—	170	80	—	170	80	—	170	Mbps
		×7	70	—	170	70	—	170	70	—	170	Mbps
		×4	40	—	170	40	—	170	40	—	170	Mbps
		×2	20	—	170	20	—	170	20	—	170	Mbps
		×1	10	—	170	10	—	170	10	—	170	Mbps
f_{HSCLK}	Input clock frequency (low-speed I/O performance pin)	×10	5	—	85	5	—	85	5	—	85	MHz
		×8	5	—	85	5	—	85	5	—	85	MHz
		×7	5	—	85	5	—	85	5	—	85	MHz
		×4	5	—	85	5	—	85	5	—	85	MHz
		×2	5	—	85	5	—	85	5	—	85	MHz
		×1	5	—	170	5	—	170	5	—	170	MHz

Symbol	Parameter	Mode	-I6, -C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
HSIODR	Data rate (low-speed I/O performance pin)	×10	100	—	170	100	—	170	100	—	170	Mbps
		×8	80	—	170	80	—	170	80	—	170	Mbps
		×7	70	—	170	70	—	170	70	—	170	Mbps
		×4	40	—	170	40	—	170	40	—	170	Mbps
		×2	20	—	170	20	—	170	20	—	170	Mbps
		×1	10	—	170	10	—	170	10	—	170	Mbps
tDUTY	Duty cycle on transmitter output clock	—	45	—	55	45	—	55	45	—	55	%
TCCS ⁽⁴³⁾	Transmitter channel-to-channel skew	—	—	—	340	—	—	340	—	—	340	ps
t _x jitter	Output jitter (for multi supply devices)	—	—	—	500	—	—	500	—	—	500	ps
t _{RISE}	Rise time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{FALL}	Fall time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{LOCK}	Time required for the PLL to lock from the end of device configuration.	—	—	—	1	—	—	1	—	—	1	ms

⁽⁴³⁾ TCCS specifications apply to I/O banks from the same side only.

True Mini-LVDS and Emulated Mini-LVDS_E_3R Transmitter Timing Specifications

Table 38: True Mini-LVDS and Emulated Mini-LVDS_E_3R Transmitter Timing Specifications for MAX 10 Dual Supply Devices—Preliminary

True **mini-LVDS** transmitter is only supported at the bottom I/O bank. Emulated **mini-LVDS_E_3R** transmitter is supported at the output pin of all I/O banks.

Symbol	Parameter	Mode	-I6, -C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
f_{HSCLK}	Input clock frequency (high-speed I/O performance pin)	×10	5	—	155	5	—	150	5	—	155	MHz
		×8	5	—	155	5	—	150	5	—	155	MHz
		×7	5	—	155	5	—	150	5	—	155	MHz
		×4	5	—	155	5	—	150	5	—	155	MHz
		×2	5	—	155	5	—	150	5	—	155	MHz
		×1	5	—	310	5	—	300	5	—	310	MHz
$HSIODR$	Data rate (high-speed I/O performance pin)	×10	100	—	310	100	—	300	100	—	310	Mbps
		×8	80	—	310	80	—	300	80	—	310	Mbps
		×7	70	—	310	70	—	300	70	—	310	Mbps
		×4	40	—	310	40	—	300	40	—	310	Mbps
		×2	20	—	310	20	—	300	20	—	310	Mbps
		×1	10	—	310	10	—	300	10	—	310	Mbps
f_{HSCLK}	Input clock frequency (low-speed I/O performance pin)	×10	5	—	150	5	—	145	5	—	150	MHz
		×8	5	—	150	5	—	145	5	—	150	MHz
		×7	5	—	150	5	—	145	5	—	150	MHz
		×4	5	—	150	5	—	145	5	—	150	MHz
		×2	5	—	150	5	—	145	5	—	150	MHz
		×1	5	—	300	5	—	290	5	—	300	MHz

Symbol	Parameter	Mode	-I6, -C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
HSIODR	Data rate (low-speed I/O performance pin)	×10	100	—	300	100	—	290	100	—	300	Mbps
		×8	80	—	300	80	—	290	80	—	300	Mbps
		×7	70	—	300	70	—	290	70	—	300	Mbps
		×4	40	—	300	40	—	290	40	—	300	Mbps
		×2	20	—	300	20	—	290	20	—	300	Mbps
		×1	10	—	300	10	—	290	10	—	300	Mbps
t _{DUTY}	Duty cycle on transmitter output clock	—	45	—	55	45	—	55	45	—	55	%
TCCS ⁽⁴⁴⁾	Transmitter channel-to-channel skew	—	—	—	340	—	—	340	—	—	340	ps
t _{X Jitter}	Output jitter (for multi supply devices)	—	—	—	500	—	—	500	—	—	500	ps
t _{RISE}	Rise time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{FALL}	Fall time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{LOCK}	Time required for the PLL to lock from the end of device configuration.	—	—	—	1	—	—	1	—	—	1	ms

⁽⁴⁴⁾ TCCS specifications apply to I/O banks from the same side only.

True LVDS Transmitter Timing

Single Supply Devices True LVDS Transmitter Timing Specifications

Table 39: True LVDS Transmitter Timing Specifications for MAX 10 Single Supply Devices—Preliminary

True LVDS transmitter is only supported at the bottom I/O bank.

Symbol	Parameter	Mode	-C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
f_{HSCLK}	Input clock frequency	×10	5	—	145	5	—	97.5	5	—	100	MHz
		×8	5	—	145	5	—	97.5	5	—	100	MHz
		×7	5	—	145	5	—	97.5	5	—	100	MHz
		×4	5	—	145	5	—	97.5	5	—	100	MHz
		×2	5	—	145	5	—	97.5	5	—	100	MHz
		×1	5	—	290	5	—	195	5	—	200	MHz
HSIODR	Data rate	×10	100	—	290	100	—	195	100	—	200	Mbps
		×8	80	—	290	80	—	195	80	—	200	Mbps
		×7	70	—	290	70	—	195	70	—	200	Mbps
		×4	40	—	290	40	—	195	40	—	200	Mbps
		×2	20	—	290	20	—	195	20	—	200	Mbps
		×1	10	—	290	10	—	195	10	—	200	Mbps
t_{DUTY}	Duty cycle on transmitter output clock	—	45	—	55	45	—	55	45	—	55	%
TCCS ⁽⁴⁵⁾	Transmitter channel-to-channel skew	—	—	—	340	—	—	340	—	—	340	ps

⁽⁴⁵⁾ TCCS specifications apply to I/O banks from the same side only.

Symbol	Parameter	Mode	-C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
t_x Jitter	Output jitter	—	—	—	1,000	—	—	1,000	—	—	1,000	ps
t_{RISE}	Rise time	20 – 80%, $C_{LOAD} = 5 \text{ pF}$	—	500	—	—	500	—	—	500	—	ps
t_{FALL}	Fall time	20 – 80%, $C_{LOAD} = 5 \text{ pF}$	—	500	—	—	500	—	—	500	—	ps
t_{LOCK}	Time required for the PLL to lock from the end of device configuration.	—	—	—	1	—	—	1	—	—	1	ms

Dual Supply Devices True LVDS Transmitter Timing Specifications

Table 40: True LVDS Transmitter Timing Specifications for MAX 10 Dual Supply Devices—Preliminary

True LVDS transmitter is only supported at the bottom I/O bank.

Symbol	Parameter	Mode	-I6, -C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
f_{HSCLK}	Input clock frequency	×10	5	—	360 ⁽⁴⁶⁾ , 335 ⁽⁴⁷⁾	5	—	290	5	—	300	MHz
		×8	5	—	360	5	—	310	5	—	320	MHz
		×7	5	—	360 ⁽⁴⁶⁾ , 335 ⁽⁴⁷⁾	5	—	290	5	—	300	MHz
		×4	5	—	360	5	—	310	5	—	320	MHz
		×2	5	—	360	5	—	310	5	—	320	MHz
		×1	5	—	360	5	—	310	5	—	320	MHz

⁽⁴⁶⁾ Applicable to -I6 speed grade.

⁽⁴⁷⁾ Applicable to -C7 and -I7 speed grades.

Symbol	Parameter	Mode	-I6, -C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
HSIODR	Data rate	×10	100	—	720 ⁽⁴⁶⁾ , 670 ⁽⁴⁷⁾	100	—	580	100	—	600	Mbps
		×8	80	—	720	80	—	620	80	—	640	Mbps
		×7	70	—	720 ⁽⁴⁶⁾ , 670 ⁽⁴⁷⁾	70	—	580	70	—	600	Mbps
		×4	40	—	720	40	—	620	40	—	640	Mbps
		×2	20	—	720	20	—	620	20	—	640	Mbps
		×1	10	—	360	10	—	310	10	—	320	Mbps
t _{DUTY}	Duty cycle on transmitter output clock	—	45	—	55	45	—	55	45	—	55	%
TCCS ⁽⁴⁸⁾	Transmitter channel-to-channel skew	—	—	—	340	—	—	340	—	—	340	ps
t _{x Jitter}	Output jitter	—	—	—	500	—	—	500	—	—	500	ps
t _{RISE}	Rise time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{FALL}	Fall time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{LOCK}	Time required for the PLL to lock from the end of device configuration.	—	—	—	1	—	—	1	—	—	1	ms

⁽⁴⁸⁾ TCCS specifications apply to I/O banks from the same side only.

Emulated LVDS_E_3R, SLVS, and Sub-LVDS Transmitter Timing Specifications

Single Supply Devices Emulated LVDS_E_3R Transmitter Timing Specifications

Table 41: Emulated LVDS_E_3R Transmitter Timing Specifications for MAX 10 Single Supply Devices—Preliminary

Emulated LVDS_E_3R transmitters are supported at the output pin of all I/O banks.

Symbol	Parameter	Mode	-C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
f_{HSCLK}	Input clock frequency (high-speed I/O performance pin)	×10	5	—	142.5	5	—	97.5	5	—	100	MHz
		×8	5	—	142.5	5	—	97.5	5	—	100	MHz
		×7	5	—	142.5	5	—	97.5	5	—	100	MHz
		×4	5	—	142.5	5	—	97.5	5	—	100	MHz
		×2	5	—	142.5	5	—	97.5	5	—	100	MHz
		×1	5	—	285	5	—	195	5	—	200	MHz
$HSIODR$	Data rate (high-speed I/O performance pin)	×10	100	—	285	100	—	195	100	—	200	Mbps
		×8	80	—	285	80	—	195	80	—	200	Mbps
		×7	70	—	285	70	—	195	70	—	200	Mbps
		×4	40	—	285	40	—	195	40	—	200	Mbps
		×2	20	—	285	20	—	195	20	—	200	Mbps
		×1	10	—	285	10	—	195	10	—	200	Mbps
f_{HSCLK}	Input clock frequency (low-speed I/O performance pin)	×10	5	—	100	5	—	100	5	—	100	MHz
		×8	5	—	100	5	—	100	5	—	100	MHz
		×7	5	—	100	5	—	100	5	—	100	MHz
		×4	5	—	100	5	—	100	5	—	100	MHz
		×2	5	—	100	5	—	100	5	—	100	MHz
		×1	5	—	200	5	—	200	5	—	200	MHz

Symbol	Parameter	Mode	-C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
HSIODR	Data rate (low-speed I/O performance pin)	×10	100	—	200	100	—	200	100	—	200	Mbps
		×8	80	—	200	80	—	200	80	—	200	Mbps
		×7	70	—	200	70	—	200	70	—	200	Mbps
		×4	40	—	200	40	—	200	40	—	200	Mbps
		×2	20	—	200	20	—	200	20	—	200	Mbps
		×1	10	—	200	10	—	200	10	—	200	Mbps
t _{DUTY}	Duty cycle on transmitter output clock	—	45	—	55	45	—	55	45	—	55	%
TCCS ⁽⁴⁹⁾	Transmitter channel-to-channel skew	—	—	—	340	—	—	340	—	—	340	ps
t _{x jitter}	Output jitter	—	—	—	1,000	—	—	1,000	—	—	1,000	ps
t _{RISE}	Rise time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{FALL}	Fall time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{LOCK}	Time required for the PLL to lock from the end of device configuration.	—	—	—	1	—	—	1	—	—	1	ms

⁽⁴⁹⁾ TCCS specifications apply to I/O banks from the same side only.

Dual Supply Devices Emulated LVDS_E_3R, SLVS, and Sub-LVDS Transmitter Timing Specifications

Table 42: Emulated LVDS_E_3R, SLVS, and Sub-LVDS Transmitter Timing Specifications for MAX 10 Dual Supply Devices—Preliminary

Emulated LVDS_E_3R, SLVS, and Sub-LVDS transmitters are supported at the output pin of all I/O banks.

Symbol	Parameter	Mode	-I6, -C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
f_{HSCLK}	Input clock frequency (high-speed I/O performance pin)	×10	5	—	300	5	—	267.5	5	—	275	MHz
		×8	5	—	300	5	—	267.5	5	—	275	MHz
		×7	5	—	300	5	—	267.5	5	—	275	MHz
		×4	5	—	300	5	—	267.5	5	—	275	MHz
		×2	5	—	300	5	—	267.5	5	—	275	MHz
		×1	5	—	300	5	—	267.5	5	—	275	MHz
f_{HSODR}	Data rate (high-speed I/O performance pin)	×10	100	—	600	100	—	535	100	—	550	Mbps
		×8	80	—	600	80	—	535	80	—	550	Mbps
		×7	70	—	600	70	—	535	70	—	550	Mbps
		×4	40	—	600	40	—	535	40	—	550	Mbps
		×2	20	—	600	20	—	535	20	—	550	Mbps
		×1	10	—	300	10	—	267.5	10	—	275	Mbps
f_{HSCLK}	Input clock frequency (low-speed I/O performance pin)	×10	5	—	150	5	—	145	5	—	150	MHz
		×8	5	—	150	5	—	145	5	—	150	MHz
		×7	5	—	150	5	—	145	5	—	150	MHz
		×4	5	—	150	5	—	145	5	—	150	MHz
		×2	5	—	150	5	—	145	5	—	150	MHz
		×1	5	—	300	5	—	290	5	—	300	MHz

Symbol	Parameter	Mode	-I6, -C7, -I7			-A7			-C8			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
HSIODR	Data rate (low-speed I/O performance pin)	×10	100	—	300	100	—	290	100	—	300	Mbps
		×8	80	—	300	80	—	290	80	—	300	Mbps
		×7	70	—	300	70	—	290	70	—	300	Mbps
		×4	40	—	300	40	—	290	40	—	300	Mbps
		×2	20	—	300	20	—	290	20	—	300	Mbps
		×1	10	—	300	10	—	290	10	—	300	Mbps
t _{DUTY}	Duty cycle on transmitter output clock	—	45	—	55	45	—	55	45	—	55	%
TCCS ⁽⁵⁰⁾	Transmitter channel-to-channel skew	—	—	—	340	—	—	340	—	—	340	ps
t _{x Jitter}	Output jitter	—	—	—	500	—	—	500	—	—	500	ps
t _{RISE}	Rise time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{FALL}	Fall time	20 – 80%, C _{LOAD} = 5 pF	—	500	—	—	500	—	—	500	—	ps
t _{LOCK}	Time required for the PLL to lock from the end of device configuration.	—	—	—	1	—	—	1	—	—	1	ms

⁽⁵⁰⁾ TCCS specifications apply to I/O banks from the same side only.

LVDS, TMDS, HiSpi, SLVS, and Sub-LVDS Receiver Timing Specifications**Single Supply Devices LVDS Receiver Timing Specifications****Table 43: LVDS Receiver Timing Specifications for MAX 10 Single Supply Devices—Preliminary**

LVDS receivers are supported at all banks.

Symbol	Parameter	Mode	-C7, -I7		-A7		-C8		Unit
			Min	Max	Min	Max	Min	Max	
f_{HSCLK}	Input clock frequency (high-speed I/O performance pin)	×10	5	145	5	97.5	5	100	MHz
		×8	5	145	5	97.5	5	100	MHz
		×7	5	145	5	97.5	5	100	MHz
		×4	5	145	5	97.5	5	100	MHz
		×2	5	145	5	97.5	5	100	MHz
		×1	5	290	5	195	5	200	MHz
HSIODR	Data rate (high-speed I/O performance pin)	×10	100	290	100	195	100	200	Mbps
		×8	80	290	80	195	80	200	Mbps
		×7	70	290	70	195	70	200	Mbps
		×4	40	290	40	195	40	200	Mbps
		×2	20	290	20	195	20	200	Mbps
		×1	10	290	10	195	10	200	Mbps
f_{HSCLK}	Input clock frequency (low-speed I/O performance pin)	×10	5	100	5	100	5	100	MHz
		×8	5	100	5	100	5	100	MHz
		×7	5	100	5	100	5	100	MHz
		×4	5	100	5	100	5	100	MHz
		×2	5	100	5	100	5	100	MHz
		×1	5	200	5	200	5	200	MHz

Symbol	Parameter	Mode	-C7, -I7		-A7		-C8		Unit
			Min	Max	Min	Max	Min	Max	
HSIODR	Data rate (low-speed I/O performance pin)	×10	100	200	100	200	100	200	Mbps
		×8	80	200	80	200	80	200	Mbps
		×7	70	200	70	200	70	200	Mbps
		×4	40	200	40	200	40	200	Mbps
		×2	20	200	20	200	20	200	Mbps
		×1	10	200	10	200	10	200	Mbps
SW	Sampling window (high-speed I/O performance pin)	—	—	700	—	700	—	700	ps
	Sampling window (low-speed I/O performance pin)	—	—	900	—	900	—	900	ps
t_x Jitter	Input jitter	—	—	1,000	—	1,000	—	1,000	ps
t_{LOCK}	Time required for the PLL to lock from the end of device configuration.	—	—	1	—	1	—	1	ms

Dual Supply Devices LVDS, TMDS, HiSpi, SLVS, and Sub-LVDS Receiver Timing Specifications

Table 44: LVDS, TMDS, HiSpi, SLVS, and Sub-LVDS Receiver Timing Specifications for MAX 10 Dual Supply Devices—Preliminary

LVDS, TMDS, HiSpi, SLVS, and Sub-LVDS receivers are supported at all banks.

Symbol	Parameter	Mode	-I6, -C7, -I7		-A7		-C8		Unit
			Min	Max	Min	Max	Min	Max	
f_{HSCLK}	Input clock frequency (high-speed I/O performance pin)	×10	5	360	5	310	5	320	MHz
		×8	5	360	5	310	5	320	MHz
		×7	5	360	5	310	5	320	MHz
		×4	5	360	5	310	5	320	MHz
		×2	5	360	5	310	5	320	MHz
		×1	5	360	5	310	5	320	MHz
$HSIODR$	Data rate (high-speed I/O performance pin)	×10	100	720	100	620	100	640	Mbps
		×8	80	720	80	620	80	640	Mbps
		×7	70	720	70	620	70	640	Mbps
		×4	40	720	40	620	40	640	Mbps
		×2	20	720	20	620	20	640	Mbps
		×1	10	360	10	310	10	320	Mbps
f_{HSCLK}	Input clock frequency (low-speed I/O performance pin)	×10	5	150	5	145	5	150	MHz
		×8	5	150	5	145	5	150	MHz
		×7	5	150	5	145	5	150	MHz
		×4	5	150	5	145	5	150	MHz
		×2	5	150	5	145	5	150	MHz
		×1	5	300	5	290	5	300	MHz

Symbol	Parameter	Mode	-I6, -C7, -I7		-A7		-C8		Unit
			Min	Max	Min	Max	Min	Max	
HSIODR	Data rate (low-speed I/O performance pin)	×10	100	300	100	290	100	300	Mbps
		×8	80	300	80	290	80	300	Mbps
		×7	70	300	70	290	70	300	Mbps
		×4	40	300	40	290	40	300	Mbps
		×2	20	300	20	290	20	300	Mbps
		×1	10	300	10	290	10	300	Mbps
SW	Sampling window	—	—	400	—	400	—	400	ps
t_x Jitter	Input jitter	—	—	500	—	500	—	500	ps
t_{LOCK}	Time required for the PLL to lock from the end of device configuration.	—	—	1	—	1	—	1	ms

Memory Output Clock Jitter Specifications

MAX 10 devices support external memory interfaces up to 300 MHz. The external memory interfaces for MAX 10 devices calibrate automatically. The memory output clock jitter measurements are for 200 consecutive clock cycles.

The clock jitter specification applies to memory output clock pins generated using DDIO circuits clocked by a PLL output routed on a global clock network.

DDR3 and LPDDR2 SDRAM memory interfaces are only supported on the fast speed grade device.

Table 45: Memory Output Clock Jitter Specifications for MAX 10 Devices—Preliminary

Parameter	Symbol	-6 Speed Grade		-7 Speed Grade		Unit
		Min	Max	Min	Max	
Clock period jitter	$t_{JIT(per)}$	-100	100	-125	125	ps
Cycle-to-cycle period jitter	$t_{JIT(cc)}$	—	200	—	250	ps

Related Information

Literature: External Memory Interfaces

Provides more information about external memory system performance specifications, board design guidelines, timing analysis, simulation, and debugging information.

Configuration Specifications

This section provides configuration specifications and timing for MAX 10 devices.

JTAG Timing Parameters

Table 46: JTAG Timing Parameters for MAX 10 Devices—Preliminary

The values are based on $C_L = 10 \text{ pF}$ of TDO .

The affected Boundary Scan Test (BST) instructions are SAMPLE/PRELOAD, EXTEST, INTEST, and CHECK_STATUS.

Symbol	Parameter	Non-BST and non-CONFIG_IO Operation		BST and CONFIG_IO Operation		Unit
		Minimum	Maximum	Minimum	Maximum	
t_{JCP}	TCK clock period	40	—	50	—	ns
t_{JCH}	TCK clock high time	20	—	25	—	ns
t_{JCL}	TCK clock low time	20	—	25	—	ns
t_{JPSU_TDI}	JTAG port setup time	2	—	2	—	ns
t_{JPSU_TMS}	JTAG port setup time	3	—	3	—	ns
t_{JPH}	JTAG port hold time	10	—	10	—	ns
t_{JPCO}	JTAG port clock to output	—	<ul style="list-style-type: none">• 15 (for $V_{CCIO} = 3.3, 3.0, \text{ and } 2.5 \text{ V}$)• 17 (for $V_{CCIO} = 1.8 \text{ and } 1.5 \text{ V}$)	—	<ul style="list-style-type: none">• 18 (for $V_{CCIO} = 3.3, 3.0, \text{ and } 2.5 \text{ V}$)• 20 (for $V_{CCIO} = 1.8 \text{ and } 1.5 \text{ V}$)	ns

Symbol	Parameter	Non-BST and non-CONFIG_IO Operation		BST and CONFIG_IO Operation		Unit
		Minimum	Maximum	Minimum	Maximum	
t_{JPZX}	JTAG port high impedance to valid output	—	<ul style="list-style-type: none"> • 15 (for $V_{CCIO} = 3.3$, 3.0, and 2.5 V) • 17 (for $V_{CCIO} = 1.8$ and 1.5 V) 	—	<ul style="list-style-type: none"> • 15 (for $V_{CCIO} = 3.3$, 3.0, and 2.5 V) • 17 (for $V_{CCIO} = 1.8$ and 1.5 V) 	ns
t_{JPXZ}	JTAG port valid output to high impedance	—	<ul style="list-style-type: none"> • 15 (for $V_{CCIO} = 3.3$, 3.0, and 2.5 V) • 17 (for $V_{CCIO} = 1.8$ and 1.5 V) 	—	<ul style="list-style-type: none"> • 15 (for $V_{CCIO} = 3.3$, 3.0, and 2.5 V) • 17 (for $V_{CCIO} = 1.8$ and 1.5 V) 	ns

POR Specifications

Table 47: POR Delay Specifications for MAX 10 Devices—Preliminary

POR Delay	Condition	Minimum	Maximum	Unit
Don't Care	Instant-on enabled	No delay		—
Fast	Instant-on disabled	3	9	ms
Standard	Instant-on disabled	50	200	ms

Remote System Upgrade Circuitry Timing Specifications

Table 48: Remote System Upgrade Circuitry Timing Specifications for MAX 10 Devices—Preliminary

Parameter	Device	Minimum	Maximum	Unit
$t_{MAX_RU_CLK}$	All	—	40	MHz
$t_{RU_nCONFIG}$	10M02, 10M04, 10M08, 10M16, 10M25	250	—	ns
	10M40, 10M50	350	—	ns

Parameter	Device	Minimum	Maximum	Unit
$t_{RU_nRSTIMER}$	10M02, 10M04, 10M08, 10M16, 10M25	300	—	ns
	10M40, 10M50	500	—	ns

User Watchdog Internal Circuitry Timing Specifications

Table 49: User Watchdog Timer Specifications for MAX 10 Devices—Preliminary

The specifications are subject to PVT changes.

Parameter	Device	Minimum	Typical	Maximum	Unit
User watchdog frequency	10M02, 10M04, 10M08, 10M16, 10M25	3.4	5.1	7.3	MHz
	10M40, 10M50	2.2	3.3	4.8	MHz

Uncompressed Raw Binary File (.rbf) Sizes

Table 50: Uncompressed .rbf Sizes and Internal Configuration Time for MAX 10 Devices—Preliminary

The internal configuration time is based on the uncompressed, unencrypted, and without memory initialization files. Turn on instant-on feature to measure the internal configuration time. The internal configuration time measurement is from the minimum value of V_{CC_ONE} (for single supply devices) or V_{CC} (for dual supply devices) to user mode entry.

Device	CFM Data Size (bits)		Internal Configuration Time (ms)
	Without Memory Initialization	With Memory Initialization	
10M02	554,000	676,000	3
10M04	1,540,000	1,880,000	4
10M08	1,540,000	1,880,000	4
10M16	2,800,000	3,430,000	5
10M25	4,140,000	4,780,000	5
10M40	7,840,000	9,670,000	9
10M50	7,840,000	9,670,000	9

Related Information**MAX 10 FPGA Configuration User Guide**

Provides more information about instant-on feature.

Programmable IOE Delay

Programmable IOE Delay On Row Pins

Table 51: IOE Programmable Delay on Row Pins for MAX 10 Devices—Preliminary

The incremental values for the settings are generally linear. For exact values of each setting, refer to the **Assignment Name** column in the latest version of the Quartus II software.

The minimum and maximum offset timing numbers are in reference to setting '0' as available in the Quartus II software.

Parameter	Paths Affected	Number of Settings	Minimum Offset	Maximum Offset						Unit	
				Fast Corner		Slow Corner					
				-I7	-C8	-C7	-C8	-I7	-A7		
Input delay from pin to internal cells	Pad to I/O dataout to core	7	0	0.782	0.838	1.738	1.799	1.796	1.673	ns	
Input delay from pin to input register	Pad to I/O input register	8	0	0.887	0.953	1.973	2.040	2.042	1.902	ns	
Delay from output register to output pin	I/O output register to pad	2	0	0.460	0.493	1.027	1.073	1.061	0.977	ns	

Programmable IOE Delay for Column Pins

Table 52: IOE Programmable Delay on Column Pins for MAX 10 Devices—Preliminary

The incremental values for the settings are generally linear. For exact values of each setting, refer to the **Assignment Name** column in the latest version of the Quartus II software.

The minimum and maximum offset timing numbers are in reference to setting ‘0’ as available in the Quartus II software.

Parameter	Paths Affected	Number of Settings	Minimum Offset	Maximum Offset						Unit	
				Fast Corner		Slow Corner					
				-I7	-C8	-C7	-C8	-I7	-A7		
Input delay from pin to internal cells	Pad to I/O dataout to core	7	0	0.777	0.833	1.73	1.79	1.788	1.666	ns	
Input delay from pin to input register	Pad to I/O input register	8	0	0.877	0.942	1.951	2.017	2.018	1.882	ns	
Delay from output register to output pin	I/O output register to pad	2	0	0.417	0.447	0.931	0.973	0.961	0.887	ns	

Glossary

Table 53: Glossary

Term	Definition
Preliminary	Some tables show the designation as “Preliminary”. Preliminary characteristics are created using simulation results, process data, and other known parameters. Final numbers are based on actual silicon characterization and testing. The numbers reflect the actual performance of the device under worst-case silicon process, voltage, and junction temperature conditions. There are no preliminary designations on finalized tables.
R _L	Receiver differential input discrete resistor (external to MAX 10 devices).

Term	Definition
RSKM (Receiver input skew margin)	HIGH-SPEED I/O block: The total margin left after accounting for the sampling window and TCCS. $RSKM = (TUI - SW - TCCS) / 2$.
Sampling window (SW)	HIGH-SPEED I/O Block: The period of time during which the data must be valid to capture it correctly. The setup and hold times determine the ideal strobe position in the sampling window.
Single-ended voltage referenced I/O standard	<p>The AC input signal values indicate the voltage levels at which the receiver must meet its timing specifications. The DC input signal values indicate the voltage levels at which the final logic state of the receiver is unambiguously defined. After the receiver input crosses the AC value, the receiver changes to the new logic state.</p> <p>The new logic state is then maintained as long as the input stays beyond the DC threshold. This approach is intended to provide predictable receiver timing in the presence of input waveform ringing.</p>
t_C	High-speed receiver/transmitter input and output clock period.
TCCS (Channel-to-channel-skew)	HIGH-SPEED I/O block: The timing difference between the fastest and slowest output edges, including t_{CO} variation and clock skew. The clock is included in the TCCS measurement.
t_{cin}	Delay from clock pad to I/O input register.
t_{CO}	Delay from clock pad to I/O output.
t_{cout}	Delay from clock pad to I/O output register.
t_{DUTY}	HIGH-SPEED I/O Block: Duty cycle on high-speed transmitter output clock.
t_{FALL}	Signal high-to-low transition time (80–20%).
t_H	Input register hold time.
Timing Unit Interval (TUI)	HIGH-SPEED I/O block: The timing budget allowed for skew, propagation delays, and data sampling window. $(TUI = 1/(Receiver\ Input\ Clock\ Frequency\ Multiplication\ Factor)) = t_C/w$.
$t_{INJITTER}$	Period jitter on PLL clock input.
$t_{OUTJITTER_DEDCLK}$	Period jitter on dedicated clock output driven by a PLL.
$t_{OUTJITTER_IO}$	Period jitter on general purpose I/O driven by a PLL.
t_{pllcin}	Delay from PLL inclk pad to I/O input register.
$t_{pllcout}$	Delay from PLL inclk pad to I/O output register.
t_{RISE}	Signal low-to-high transition time (20–80%).

Term	Definition
t_{SU}	Input register setup time.
$V_{CM(DC)}$	DC common mode input voltage.
$V_{DIF(AC)}$	AC differential input voltage: The minimum AC input differential voltage required for switching.
$V_{DIF(DC)}$	DC differential input voltage: The minimum DC input differential voltage required for switching.
V_{ICM}	Input common mode voltage: The common mode of the differential signal at the receiver.
V_{ID}	Input differential Voltage Swing: The difference in voltage between the positive and complementary conductors of a differential transmission at the receiver.
V_{IH}	Voltage input high: The minimum positive voltage applied to the input which is accepted by the device as a logic high.
$V_{IH(AC)}$	High-level AC input voltage.
$V_{IH(DC)}$	High-level DC input voltage.
V_{IL}	Voltage input low: The maximum positive voltage applied to the input which is accepted by the device as a logic low.
$V_{IL(AC)}$	Low-level AC input voltage.
$V_{IL(DC)}$	Low-level DC input voltage.
V_{IN}	DC input voltage.
V_{OCM}	Output common mode voltage: The common mode of the differential signal at the transmitter.
V_{OD}	Output differential voltage swing: The difference in voltage between the positive and complementary conductors of a differential transmission at the transmitter. $V_{OD} = V_{OH} - V_{OL}$.
V_{OH}	Voltage output high: The maximum positive voltage from an output which the device considers is accepted as the minimum positive high level.
V_{OL}	Voltage output low: The maximum positive voltage from an output which the device considers is accepted as the maximum positive low level.
V_{OS}	Output offset voltage: $V_{OS} = (V_{OH} + V_{OL}) / 2$.
$V_{OX(AC)}$	AC differential Output cross point voltage: The voltage at which the differential output signals must cross.
V_{REF}	Reference voltage for SSTL, HSTL, and HSUL I/O Standards.

Term	Definition
V _{REF(AC)}	AC input reference voltage for SSTL, HSTL, and HSUL I/O Standards. V _{REF(AC)} = V _{REF(DC)} + noise. The peak-to-peak AC noise on V _{REF} should not exceed 2% of V _{REF(DC)} .
V _{REF(DC)}	DC input reference voltage for SSTL, HSTL, and HSUL I/O Standards.
V _{SWING (AC)}	AC differential input voltage: AC Input differential voltage required for switching.
V _{SWING (DC)}	DC differential input voltage: DC Input differential voltage required for switching.
V _{TT}	Termination voltage for SSTL, HSTL, and HSUL I/O Standards.
V _{X (AC)}	AC differential Input cross point voltage: The voltage at which the differential input signals must cross.

Document Revision History for MAX 10 FPGA Device Datasheet

Date	Version	Changes
January 2015	2015.01.23	<ul style="list-style-type: none"> Removed a note to V_{CCA} in Power Supplies Recommended Operating Conditions for MAX 10 Dual Supply Devices table. This note is not valid: All V_{CCA} pins must be connected together for EQFP package. Corrected the maximum value for t_{OUTJITTER_CCJ_IO} (F_{OUT} ≥ 100 MHz) from 60 ps to 650 ps in PLL Specifications for MAX 10 Devices table.
December 2014	2014.12.15	<ul style="list-style-type: none"> Restructured Programming/Erasure Specifications for MAX 10 Devices table to add temperature specifications that affect the data retention duration. Added statements in the I/O Pin Leakage Current section: Input channel leakage of ADC I/O pins due to hot socket is up to maximum of 1.8 mA. The input channel leakage occurs when the ADC IP core is enabled or disabled. This is applicable to all MAX 10 devices with ADC IP core, which are 10M04, 10M08, 10M16, 10M25, 10M40, and 10M50 devices. The ADC I/O pins are in Bank 1A. Added a statement in the I/O Standards Specifications section: You must perform timing closure analysis to determine the maximum achievable frequency for general purpose I/O standards. Updated SSTL-2 Class I and II I/O standard specifications for JEDEC compliance as follows: <ul style="list-style-type: none"> VIL(AC) Max: Updated from V_{REF} – 0.35 to V_{REF} – 0.31 VIH(AC) Min: Updated from V_{REF} + 0.35 to V_{REF} + 0.31

Date	Version	Changes
		<ul style="list-style-type: none">Added a note to BLVDS in Differential I/O Standards Specifications for MAX 10 Devices table: BLVDS TX is not supported in single supply devices.Added a link to MAX 10 High-Speed LVDS I/O User Guide for the list of I/O standards supported in single supply and dual supply devices.Added a statement in PLL Specifications for MAX 10 Single Supply Device table: For V36 package, the PLL specification is based on single supply devices.Added Internal Oscillator Specifications from MAX 10 Clocking and PLL User Guide.Added UFM specifications for serial interface.Updated total harmonic distortion (THD) specifications as follows:<ul style="list-style-type: none">Single supply devices: Updated from 65 dB to -65 dBDual supply devices: Updated from 70 dB to -70 dB (updated from 65 dB to -65 dB for dual function pin)Added condition for On-Chip Temperature Sensor—Absolute accuracy parameter in ADC Performance Specifications for MAX 10 Dual Supply Devices table. The condition is: with 64 samples averaging.Updated the description in Periphery Performance Specifications to mention that proper timing closure is required in design.Updated HSIODR and f_{HSCLK} specifications for x10 and x7 modes in True LVDS Transmitter Timing Specifications for MAX 10 Dual Supply Devices.Added specifications for low-speed I/O performance pin sampling window in LVDS Receiver Timing Specifications for MAX 10 Single Supply Devices table: Max = 900 ps for -C7, -I7, -A7, and -C8 speed grades.Added $t_{RU_nCONFIG}$ and $t_{RU_nRSTIMER}$ specifications for different devices in Remote System Upgrade Circuitry Timing Specifications for MAX 10 Devices table.Removed the word "internal oscillator" in User Watchdog Timer Specifications for MAX 10 Devices table to avoid confusion.Added IOE programmable delay specifications.
September 2014	2014.09.22	Initial release.